

TOOL NO.	GUIDE PIN NO.	LEAF SPRING NO.	USED OF
92036-2	126638-5	126837=1	200864-200869-200866
91016-2	126038-2	126037-1	200864 200865 200866 200869 201376

1. FOR TOOL USAGE, SEE INSTRUCTION SHEET # 7/26

APPLICATION TOOLING ENGING.
CONNECTOR PRODUCTS DIV.

					C1963 BY AMP INCORPORATED RESERVED, AMP PRODUCTS COVER PATENTS AND/OR PATENTS PEND	RED BY DEEE DENCE ON V	
		1			MATERIAL AND FRIESH MANDLES-STEEL MICKEL PLATED	AMP INCORPORATI	
41	Loc M was A	EK	_	% ha	Jaws – Steel Rlackened	WEIGHT: 7 OZ.	_
A	9/0/6-/ 3/06/38/ By 9006-2	#	200	11/9/4	WIRE - RANGE - INSULATION		
LTR		DR	СІЖ	DATE	TOLERANCE EXCEPT SCALE AS NOTED	M A ™C 91016 7	=V -
2	0.4/6/1 - 63 0 /46/ 3/14/3				NAME		_ <u>~</u>
D.	DE Danie 1)8/12/63 APP				TOOL-SPIROL PIN INSERTION		

MP 1252 REV 7/60

DIMENSIONS IN INCHES, DO NOT SCALE PRINT.